DAKOTA

Specification Sheet

QUICK LEVEL - SINGLE ELEMENTS





Code	Commercial Description	Dimensions	Conf.	Pallet	Selling Unit
TER04-4400DK	Cylinder Quick Level with scratch proof disk	-	1	200	CF
TER04-4401DK	Linear spacer screw 1 mm for cylinder system	1 mm	1	375	CF
TER04-44015DK	Linear spacer screw 1,5 mm for cylinder system	1,5 mm	1	375	CF
TER04-4402DK	Linear disposable screw 2 mm for tiles from 3 to 2	2 mm	1	375	CF
TER04-44025DK	Linear disposable screw 2.5 mm for tiles from 3 to	2,5 mm	1	375	
TER04-4403DK	Linear spacer screw 3 mm for cylinder system	3 mm	1	375	CF
TER04-4404DK	One-way screw 4mm cylinder system - 100 pcs/envelo		1	375	CF

Description

Consisting of two assembled elements (cylinder and screw). It is easy and quick to rectify any differences between tile and tile, thus obtaining a complanar and equidistant pose. The cylinder is equipped with Scratch Proof Discs that allows a secure installation and prevents any scratches on the surface in case of excessive screwing. The working range is very wide with tiles from 3 to 22 mm. Available in 1, 1, 5, 2, 3 mm joints.

Material

Made of Recycled plastic material.



Use

Used as leveling system for flooring and facade tiles and coatings of various sizes and thicknesses, especially for large sizes.

